

MAX-SERIES NOZZLES

MAX-FORCE 100 - 500 GPM (400-2000 l/min) Dual Pressure Automatic

MD12A

\$980.00

6.7 lb (3.0kg)

9.0" (22.9cm)



MD12A MAX-FORCE DUAL PRESSURE AUTOMATIC TIP 2.5" NH (65mm) - with a flow capacity of 100-500 gpm (400-2000 l/min). The nozzle may be switched between standard 100 psi (7bar) and a low pressure mode 55 psi (4bar) by twisting a knob on the front of the nozzle. The pattern adjusts from straight stream to a 120 degree wide fog. Further rotation opens the tip to flush 3/8" (10mm) debris without shutting down. Hardcoat anodized aluminum with rubber bumper. Standard inlet is 2.5"NH (65mm) rocker lug swivel.


MD-ERP-12A

MD-ER-12A

\$1500.00

10.2 lbs (4.6kg)

10" (26cm)



MD-ERP-12A 100 PSI (7bar) MAX-FORCE ELECTRIC REMOTE TIP Automatic dual-pressure control with a flow capacity of 100-500 gpm (400-2000 l/min). The nozzle may be switched between standard 100 psi (7bar) and 55 psi (4bar) by twisting a knob on the front of the nozzle. 2.5" NH (65mm) rigid rocker lug coupling is standard. For use on TFT RC monitors only.

MD-ER-12A - same as MD-ERP-12A except with 6 ft of non-terminated remote wire for custom installations. Does not have SMART STREAM technology.