



www.tft.com 3701 Innovation Way Valparaiso IN 46383-9327

800-348-2686

AA2ST-NX Task Force Tips © 2018

ADAPTER 5.0"STORZ X 6.0"NHM

Part No: AA2ST-NX



Details

ADAPTER 5.0"STORZ X 6.0"NHM RIGID TO RIGID MALE

Weight: 6.871 lbs (3.116 kg)

W. (El O()	A .l (
Water Flow Style	Adapter
Coupling Size Side A	6.0 inch (150mm)
Coupling Style Side A	Male Threads
Coupling Swiveling/Rigid Side A	Rigid
Coupling Size Side B	5.0 inch (125mm)
Coupling Style Side B	Storz
Coupling Swiveling/Rigid Side B	Rigid

Related Videos

- **LDH** Equipment
- LDH Hardware
- How to Replace Storz Locking Levers on Storz

Online Technical Support Material

New Aluminum Storz Lever

Specifications

AA2ST-NX Specifications (doc)

PRODUCT SERIES OVERVIEW

- · LDH Hardware is produced from lightweight aluminum alloy and is hardcoat anodized and powder coated for years of rugged reliability. All adapters and elbows are available in all configurations of male and female threads, as well as rocker, long handle or Storz couplings. 4", 5", and 6" Storz caps are also available for all Storz couplings.
- · LDH Hardware also includes TFT's exclusive detent swiveling elbow product line. Designed for any apparatus inlet, this unique 30° elbow allows either full time swivel to prevent unwanted supply line kinking, or any detent position can be chosen. All LDH components use the exclusive polymer ring attachment system preventing unwanted corrosion due to galvanic action.
- LDH Hardware include TFT's high flowing wyes and clappered Siamese models. The clappered Siamese allows multiple supply lines to be used for water supply to an apparatus and the wye is ideal for splitting water supply to two apparatus intakes. Both series are available with your choice of couplings, are powder coated to resist corrosion, have integrated carrying handles and are hydrostatically rated to 900 psi test pressure.