



FQS-EUPS-BIC

Task Force Tips © 2018

QUADRAFOG W/GRIP 2.5"BIC MALE

Part No: FQS-EUPS-BIC Details

QUADRAFOG W/GRIP 2.5"BIC MALE 110-470L/MIN @
700KPA 7BAR SPINNINGTEETH

Weight: 4.700 lbs (0.000 kg)

Flow Control Method	Selectable Flow at a pressure (constant gallonage, flow does not change with pattern)
Flow Rate	110-470 l/min
Coupling Size	2.5 inch (65mm)
Coupling Swiveling/Rigid (Nozzles)	Swivel (full time, even after tightening)
Connection Type	BIC Male
Pressure	700 kpa
Nozzle Body Style	Nozzle with shutoff and pistol grip
Valve Design	Ball Valve (Aluminum)
Valve Actuation Method	Lever (Folding Injection Molded Nylon)
Fog Pattern Method	stainless steel teeth (spinning)
Nozzle Bumper Material	Rubber - press fit
Certifications	NFPA/FM
Foam Expansion Performance	N/A

Related Videos

- [Pistol Grip Replacement](#)
- [Ball Handle and Valve Seat Ball Valve](#)
- [QuadraFog Series Video](#)

Online Technical Support Material

- [QuadraFog & ThunderFog Demo Sheet](#)
- [1.5in QuadraFog/QuadraCup NFPA 1964](#)
- [QuadraFog FM Approval](#)
- [Service Procedure: 1.5 QuadraFog & QuadraCup](#)
- [Manual de Instruções ThunderFog & QuadraFog](#)
- [QuadraFog & ThunderFog Instruction Manual](#)

PRODUCT SERIES OVERVIEW

- The Quadrafog Series of selectable gallonage 1 in and 1.5 in nozzles are designed for simple operation and rugged durability in wildland or structural firefighting operations. Available in tip only configurations or with a stainless steel ball shutoff and optional color coded nylon pistol grip, these series incorporate lightweight aluminum construction, reflective labeling, and stainless steel components with a protective front rubber bumper.
- The 1 in Quadrafog Series, with its fixed cut fog tooth pattern is ideal for wildfire operations or booster line operations. The 1.5in Quadrafog Series are available with either TFTs uniquely cut style of fixed fog teeth, or our popular stainless steel spinning teeth to provide a wide protective fog pattern. All models also accept either a low or multi-expansion foam aspiration attachment.
- All Quadrafog Series ball shutoff models offer TFTs unique quick change rear valve seat that requires no special tools or disassembly of the valve to change the rear seat assembly. The shut off handle can be color coded, laser engraved, and is produced from nylon to withstand harsh operating conditions without breaking or bending.