



H-2VPG

Task Force Tips © 2018

HANDLINE W/GRIP 2.5" NH (65mm)

Part No: **H-2VPG**



Flow Control Method	Automatic (constant pressure, constant gallonage, flow does not change with pattern)
Flow Rate	95-300 gpm (360-1150 l/min)
Coupling Size	2.5 inch (65mm)
Coupling Style (Nozzles)	Rocker
Coupling Swiveling/Rigid (Nozzles)	Swivel (full time, even after tightening)
Connection Type	NH Female
Pressure	100 psi (7bar)
Nozzle Body Style	Nozzle with shutoff and pistol grip
Valve Design	Slide Valve (Stainless)
Valve Actuation Method	Horseshoe (Injection Molded Nylon w/ Colored Handle)
Fog Pattern Method	Molded Rubber Teeth (fixed)
Nozzle Bumper Material	Rubber - bonded
Certifications	N/A

Details

HANDLINE W/GRIP 2.5" NH (65mm)
Automatic 100 psi (7 bar) pressure control with a flow capacity of 95-300 gpm (360-1150 l/min). Includes pressure-assisted flush without shutting down, patented slide-type valve for turbulence-free flow control, six detent flow positions, molded rubber teeth for full-fill "power fog", and "Gasket Grabber" inlet screen. Pistol grip is mounted below the valve (H-2VPGI) or behind the valve (H-2VPG). Lightweight hardcoat anodized aluminum materials for maximum resistance to corrosion and wear. 2.5" NH (65mm) rocker lug full-time swivel coupling is standard.

Weight: 8.500 lbs (3.855 kg)

Related Videos

- [Handline Upgrade for Nozzles](#)
- [Pistol Grip Replacement](#)
- [How to Adjust a TFT Slide Valve](#)
- [Handline Series](#)
- [Visual Nozzle Inspection](#)

Online Technical Support Material

- [Handline Demo Sheet](#)
- [Using Automatic Nozzles w/ Foam Eductors](#)
- [Handline & DualForce Maintenance & Service](#)
- [Handline Flow & Reaction Chart](#)
- [Folding Pistol Grip Installation](#)
- [Field Lubrication Procedure](#)
- [How to Test Proper Function of an Automatic Nozzle](#)
- [Handheld Automatic Nozzle Instructions](#)

Specifications

- [H-2VPG Specifications \(doc\)](#)
- [H-2VPG Finished Good Print](#)
- [H-2VPG Finished Good Print](#)
- [H-2VPG Finished Good Print](#)

PRODUCT SERIES OVERVIEW

- The full size Handline nozzle incorporates TFT's unique stainless steel slide valve for turbulence free flow control and includes the exclusive integrated debris screen to prevent stream quality degradation. All models accept low and multi-expansion foam attachments for increased finished foam performance.

- The full size Handline nozzle is available with 100, 75, or 55 psi operational pressure to meet any fire ground operational challenge. The high strength bonded rubber fog teeth provide a full filled pattern that pushes heat flame and smoke ahead and away from the firefighting team.

- The full size Handline nozzle comes standard with reflective labeling as well as your choice of color coded pistol grip and shut off handle. This constant pressure variable gallonage nozzle series is available in tip only, shut off, and playpipe configurations, is individually serialized, and comes with TFT's exclusive 5 year warranty.

Task Force Tips ® is a registered trademark of Task Force Tips, Inc.
TFT ® is a registered trademark of Task Force Tips, Inc.