



JT250F-65MM

Task Force Tips © 2018

THUNDERFOG TIP 65MM STORZ

Part No: JT250F-65MM
Details

THUNDERFOG TIP 65MM STORZ 95-250 GPM @ 100 PSI FIXED TEETH

Weight: 4.100 lbs (kg)

Flow Control Method	Selectable Flow at a pressure (constant gallonage, flow does not change with pattern)
Flow Rate	95 & 125 & 150 & 200 & 250 gpm (360 & 470 & 570 & 750 & 950 l/min)
Coupling Size (Nozzles)	2.5 inch (65mm)
Coupling Swiveling/Rigid (Nozzles)	Swivel (full time, even after tightening)
Connection Type	Storz
Pressure	100 psi (7bar)
Nozzle Body Style	Tip with shutoff
Valve Design	Twist Style (baffle shutoff)
Valve Actuation Method	Rotational
Fog Pattern Method	Molded Rubber Teeth (fixed)
Nozzle Bumper Material	Rubber - press fit
Certifications	NFPA/FM
Pattern Actuation Method	Manual

PRODUCT SERIES OVERVIEW

- The Thunderfog Series of selectable gallonage 1½” and 2½” nozzles are designed for simple operation and rugged durability in structural and industrial firefighting operations. Available in tip only configurations or with a stainless steel ball shutoff and optional color coded nylon pistol grip, these series incorporate lightweight aluminum construction, reflective labeling, and stainless steel components with a protective front rubber bumper.
- The 200 and 250 Thunderfog Series, are available with either TFT’s uniquely cut style of fixed fog teeth, or our popular stainless steel spinning teeth to provide a wide protective fog pattern. All models also accept either a low or multi-expansion foam aspiration attachment.
- All Thunderfog Series ball shutoff models offer TFT’s unique quick change rear valve seat that requires no special tools or disassembly of the valve to change the rear seat assembly. The shut off handle can be color coded, laser engraved, and is produced from nylon to withstands harsh operation conditions without breaking or bending.

Task Force Tips ® is a registered trademark of Task Force Tips, Inc.
TFT ® is a registered trademark of Task Force Tips, Inc.