



JTS250PS

Task Force Tips © 2018

THUNDERFOG W/GRIP 2.5" NH (64mm)

Part No: JTS250PS



Details

THUNDERFOG W/GRIP 2.5" NH (64mm)
Selectable gallonage nozzle with five flow settings of 95, 125, 150, 200, and 250 gpm @ 100 psi (360-470-570-750-950 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. Flush without shutting down. Uniquely cut fixed fog teeth or optional stainless steel spinning teeth. Quick-change rear valve seat and stainless steel shut-off ball. Pistol grip is mounted below the valve. 2.5" NH swivel rocker lug coupling is standard.

Weight: 7.000 lbs (3.175 kg)

Flow Control Method	Selectable Flow at a pressure (constant gallonage, flow does not change with pattern)
Flow Rate	95 & 125 & 150 & 200 & 250 gpm (360 & 470 & 570 & 750 & 950 l/min)
Coupling Size (Nozzles)	2.5 inch (65mm)
Coupling Style (Nozzles)	Rocker
Coupling Swiveling/Rigid (Nozzles)	Swivel (full time, even after tightening)
Connection Type	NH Female
Pressure	100 psi (7bar)
Nozzle Body Style	Nozzle with shutoff and pistol grip
Valve Design	Ball Valve (Stainless)
Valve Actuation Method	Horseshoe (Injection Molded Nylon w/ Colored Handle)
Fog Pattern Method	stainless steel teeth (spinning)
Nozzle Bumper Material	Rubber - bonded
Certifications	NFPA/FM
Foam Expansion Performance	N/A
Pattern Actuation Method	Manual

Related Videos

- [Pistol Grip Replacement](#)
- [Ball Handle and Valve Seat Ball Valve](#)
- [ThunderFog Series Video](#)
- [Visual Nozzle Inspection](#)

Online Technical Support Material

- [Service Procedure: ThunderFog](#)
- [Really Campaign - Spinning Teeth ThunderFog](#)
- [QuadraFog & ThunderFog Demo Sheet](#)
- [ThunderFog 200 Selectable Nozzles](#)
- [ThunderFog 250 Selectable Nozzles](#)
- [ThunderFog NFPA 1964](#)
- [ThunderFog FM Approval](#)
- [Service Procedure: ThunderFog](#)
- [Manual de Instruções ThunderFog & QuadraFog](#)
- [QuadraFog & ThunderFog Instruction Manual](#)

Specifications

- [JTS250PS Specifications \(doc\)](#)
- [JTS250PS Finished Good Print](#)
- [JTS250PS Finished Good Print](#)
- [JTS250PS Finished Good Print](#)

PRODUCT SERIES OVERVIEW

- The Thunderfog Series of selectable gallonage 1½" and 2½" nozzles are designed for simple operation and rugged durability in structural and industrial firefighting operations. Available in tip only configurations or with a stainless steel ball shutoff and optional color coded nylon pistol grip, these series incorporate lightweight aluminum construction, reflective labeling, and stainless steel components with a protective front rubber bumper.

- The 200 and 250 Thunderfog Series, are available with either TFT's uniquely cut style of fixed fog teeth, or our popular stainless steel spinning teeth to provide a wide protective fog pattern. All models also accept either a low or multi-expansion foam aspiration attachment.

- All Thunderfog Series ball shutoff models offer TFT's unique quick change rear valve seat that requires no special tools or disassembly of the valve to change the rear seat assembly. The shut off handle can be color coded, laser engraved, and is produced from nylon to withstands harsh operation conditions without breaking or bending.

Task Force Tips ® is a registered trademark of Task Force Tips, Inc.
TFT ® is a registered trademark of Task Force Tips, Inc.