



UEP-1500BPBP

Task Force Tips © 2018

EDUCTOR 1500LPM 4.0"BSPF X 4.0"BSPF

Part No: UEP-1500BPBP
Details

EDUCTOR 1500LPM 4.0"BSPF X 4.0"BSPF

Flow Rate	1500 lpm
Coupling Size Side A	4.0 Inch (100mm)
Coupling Style Side A	Knurled (Diamond pattern)
Coupling Swiveling/Rigid Side A	Swivel (full time, even after tightening)
Connection Type Side A	BSP Female
Coupling Size Side B	4.0 Inch (100mm)
Coupling Style Side B	Male Threads
Coupling Swiveling/Rigid Side B	Rigid
Connection Type Side B	BSP Male
Hose Coupling Size	N/A
Pressure	10 bar (150 psi)

PRODUCT SERIES OVERVIEW

- Large, easy-to-change, and simple-to-read injection rate metering head indicators allow for accurate mixing of Class A at ¼ and ½ %, and AFFF, or AFFF-AR foam concentrates at 1, 3, or 6%.
- The extra large 36" pickup hose and stainless steel wand (60, 95 and 125 gpm eductors) and the large 8 foot industrial grade UV resistant pickup hose (250 and 350 gpm eductors) are designed for use with all types of foams, including the thicker alcohol resistant concentrate -- which is easily and accurately picked up and injected into the water line.
- Unique push-button backflush feature allows for easy flushing of foam residue from the eductor, assuring functionality during the next operation.
- Quick Release Locker Ring allows eductor body to be detached from the metering head for easy storage.
- Designed for easy use with gloves.
- Maximum allowable back pressure is 130 psi (9 Bar).

Task Force Tips® is a registered trademark of Task Force Tips, Inc.
TFT® is a registered trademark of Task Force Tips, Inc.