



XX111A

Task Force Tips © 2018

BLITZFIRE MONITOR

Part No: XX111A



Monitor Configuration	Portable
Flow Rate - Monitors	0-500 gpm (0-2000 l/min)
Operation Energy Source	Manual
Monitor Inlet	2.5 inch (65mm)
Coupling Style Side A	Rocker
Connection Type Side A	NH Female
Monitor Outlet	2.5 inch (65mm)
Connection Type Side B	NH Male
Horizontal Control	N/A
Horizontal Movement (degrees)	20 left and 20 right of center
Vertical Control	N/A
Vertical Movement (degrees)	10 above to 46 above horizontal
Safety Shutoff	With Safety Shutoff
Pressure Relief Valve	No PRV
Valve Design	Slide Valve (Aluminum)
Finish	Powdercoated Dark Blue
Certifications	N/A

Details

BLITZFIRE MONITOR

Flow range up to 500 gpm (2000 l/min). The monitor features low friction inlet and outlet pivots. Outlet has built-in stream shaper. Elevation is manually adjustable between 10 and 46 degrees above horizontal. Horizontal rotation is manually adjustable 20 degrees either side of center. The SAFETY SHUT-OFF VALVE will shut off flow if monitor slides or lifts. It has six detent flow positions with a patented turbulence free slide valve for operator flow control. When the legs are folded, the carbide tips point up for carrying safety. The heavy-duty carbide tipped legs are easily folded out to a wide deployed stance. Stowed in storage bracket overall size is 29.5"L x 8.1"W x 8.5"H (74.9 x 20.6 x 21.6 cm). Standard inlet is 2.5" NH (65mm) rocker lug swivel coupling. Standard outlet is 2.5" NH (65mm) rigid male threads.

Weight: 24.500 lbs (11.113 kg)

Online Technical Support Material

- [Really Campaign - Blitzfire Portable Monitor](#)

Specifications

- [XX111A Specifications \(doc\)](#)
- [XX111A Specifications \(zip\)](#)
- [XX111A Specifications \(zip\)](#)

BLITZFIRE ® is a registered trademark of Task Force Tips, Inc.
 BLUE ® is a registered trademark of Task Force Tips, Inc.
 Task Force Tips ® is a registered trademark of Task Force Tips, Inc.
 TFT ® is a registered trademark of Task Force Tips, Inc.