



## XX111A

Task Force Tips © 2018

### BLITZFIRE MONITOR

Part No: XX111A



<b>Monitor Configuration</b>	Portable
<b>Flow Rate - Monitors</b>	0-500 gpm (0-2000 l/min)
<b>Operation Energy Source</b>	Manual
<b>Monitor Inlet</b>	2.5 Inch Rocker Lug
<b>Monitor Outlet</b>	2.5 inch (65mm)
<b>Horizontal Control</b>	N/A
<b>Horizontal Movement (degrees)</b>	20 left and 20 right of center
<b>Vertical Control</b>	N/A
<b>Vertical Movement (degrees)</b>	10 above to 46 above horizontal
<b>Safety Shutoff</b>	With Safety Shutoff
<b>Pressure Relief Valve</b>	No PRV
<b>Valve Design</b>	Slide Valve (Aluminum)
<b>Finish</b>	Powdercoated Dark Blue
<b>Certifications</b>	N/A

### Details

#### BLITZFIRE MONITOR

Flow range up to 500 gpm (2000 l/min). The monitor features low friction inlet and outlet pivots. Outlet has built-in stream shaper. Elevation is manually adjustable between 10 and 46 degrees above horizontal. Horizontal rotation is manually adjustable 20 degrees either side of center. The SAFETY SHUT-OFF VALVE will shut off flow if monitor slides or lifts. It has six detent flow positions with a patented turbulence free slide valve for operator flow control. When the legs are folded, the carbide tips point up for carrying safety. The heavy-duty carbide tipped legs are easily folded out to a wide deployed stance. Stowed in storage bracket overall size is 29.5"L x 8.1"W x 8.5"H (74.9 x 20.6 x 21.6 cm). Standard inlet is 2.5" NH (65mm) rocker lug swivel coupling. Standard outlet is 2.5" NH (65mm) rigid male threads.

**Weight: 24.500 lbs (11.113 kg)**

#### Online Technical Support Material

- [Really Campaign - Blitzfire Portable Monitor](#)

#### Specifications

- [XX111A Specifications \(doc\)](#)
- [XX111A Specifications \(zip\)](#)
- [XX111A Specifications \(zip\)](#)