



Y1-E83A

Task Force Tips © 2018

EF1 RC 2.0"NPTF INLET

Part No: Y1-E83A



Monitor Configuration	Fixed Mount
Flow Rate - Monitors	0-200 gpm (0-757 l/min)
Operation Energy Source	Electric (12/24 vdc)
Monitor Inlet	2.0 inch (52 mm)
Coupling Swiveling/Rigid Side A	Rigid
Connection Type Side A	NPT Female
Monitor Outlet	1.5 inch (38mm)
Coupling Style Side B	Male Threads
Coupling Swiveling/Rigid Side B	Rigid
Connection Type Side B	NPSH Male
Horizontal Control	N/A
Horizontal Movement (degrees)	270 degrees
Vertical Control	N/A
Vertical Movement (degrees)	45 below to 90 above horizontal
Pressure Relief Valve	No PRV
Valve Design	No Valve
Finish	Powdercoated Stardust Silver
Certifications	N/A
Hazardous Location Certification	N/A

Details

EF1 RC 2.0"NPTF INLET 1.5"NPSHM OUTLET
The EF1 remotely controlled monitor is compact with a large, efficient waterway capable of flowing up to 200 gpm (757 l/min). Perfect for wildland apparatus or interface apparatus around the globe. At less than 13" tall (without nozzle) the EF1 is an ideal forestry bumper turret. The monitor is equipped with controls for monitor horizontal rotation, elevation, nozzle pattern, programmable PARK and oscillate. The EF1 is hard coat anodized aluminum alloy and powder coated and the factory installed plug for power and communication wires, electric drives and control box are waterproof.

Weight: 17.300 lbs (kg)

Online Technical Support Material

- [MANUAL: EF1 RC MONITOR](#)

PRODUCT SERIES OVERVIEW

- The EF1 remotely controlled monitor is compact with a large, efficient waterway capable of flowing up to 200 gpm (757 l/min).
- The EF1 is TFT's most compact RC monitor at 12.6" (319 mm) yet its 1-1/2" (38 mm) waterway is capable of flowing from 40 to 200 gpm (150 - 760 l/min).
- Wiring is reduced to a minimum and installs easily using a one plug connection. With a variety of inlet options, the EF1 quickly mounts onto smaller brush trucks or conversions.