



Y2-T04A

Task Force Tips © 2018

TORNADO TILLER 3.0"ANSI 150 INLET

Part No: Y2-T04A
Details

TORNADO TILLER 3.0"ANSI 150 INLET 1.5"NH MALE
OUTLET

Weight: 18.100 lbs (kg)

Monitor Configuration	Fixed Mount
Flow Rate - Monitors	0-500 gpm (0-2000 l/min)
Operation Energy Source	Manual
Monitor Inlet	3 Inch ANSI 150
Monitor Outlet	1 1/2 inch (25mm) NH Male
Horizontal Control	Tiller Bar with Lock Knob
Horizontal Movement (degrees)	Continuous 360
Vertical Control	Tiller Bar with Lock Knob
Vertical Movement (degrees)	45 below to 90 above horizontal
Safety Shutoff	No Safety Shutoff
Pressure Relief Valve	No PRV
Valve Design	No Valve
Finish	Powdercoated Stardust Silver
Certifications	N/A

PRODUCT SERIES OVERVIEW

- The Tornado Monitor is the ideal choice for a manual or remote control monitor for apparatus front bumper applications or industrial fixed system installations. With a maximum flow rating of 500gpm, the Tornado monitor series can be configured with a wide choice of nozzles and an integrated stainless shut off valve.
- The Tornado Monitor is designed with locking, quick connect fittings for easy removal when servicing apparatus as well as your choice of joystick, toggle switch, tether, or RF controller. All RC controlled nozzles incorporate TFT's unique Smart Stream Technology that allows precise pattern control, and prevents excess water flow during pattern selection by preventing unintended nozzle flushing.
- The Tornado Monitor is manufactured from lightweight high strength aluminum alloy that is hard coat anodized and powder coated for ultimate corrosion protection. All electronics in the remote control models, including the hazardous location ATEX versions, are designed for reliable operation in rugged fireground environments.